

Sliding Panel Saw P305



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



**Quick and secure
locking wood
pressure**



**Miter fence with 0°
to 45° adjustment
for small cutting
jobs (optimal)**



**Overhead saw blade
guard (optional)**



**Efficient dust
collection system**

Specification

ITEM	MODEL	P305 2,500mm	P305 3,200 mm
Sliding table dimension		2,500x360	3,200x360
Cast iron table		548 x 896 mm	548 x 896 mm
Extension table (rear)		952 x 896 mm	952 x 896 mm
Extension table (front)		320x830 mm	320x830 mm
Table size		1,500 x1,726 mm	1,500 x1,726 mm
Round rail		Φ40	Φ40
Main saw blade (max.)		305 mm (355 mm)	305 mm (355 mm)
Main saw bore		30 mm	30 mm
Max. cutting height with blade 305 mm at 90° (335mm)		90 mm (115 mm)	90 mm (115 mm)
Max. cutting height with blade 305 mm at 45° (335mm)		62 mm (70mm)	62 mm (70mm)
Main motor power (3ph)		5 HP (3,750kw)	5 HP (3,750kw)
Main blade speed		4,000 r.p.m	4,000 r.p.m
Scoring saw blade		120 mm	120 mm
Scoring saw blade bore		20 mm	20 mm
Scoring blade motor power (optimal)		¼ HP (0.56 kw)	¼ HP (0.56 kw)
Scoring blade speed		8,000 r.p.m	8,000 r.p.m
Cutting width		1,300 mm	1,300 mm
Main saw blade tilting adjustment		Manual (0°~45°)	Manual (0°~45°)
Saw guard		Simple (overload guard optional)	Simple (overload guard optional)
Dust collection system		120 mm / 60 mm	120 mm / 60 mm
N.W/G.W/MEAS.(MACHINE)		500/600 kgs (2.110x1,130x1,120 mm)	500/600 kgs (2.110x1,130x1,120 mm)
N.W/G.W/MEAS. (sliding table)		69/75 kgs (2,610x430x240mm)	80/103 kgs (3,300x 430x220 mm)
N.W/G.W/MEAS.(overhead guard)		39/40 kgs (1420x980x120mm) + ½ kgs (640x210x210 mm)	
Ctn. Q'ty:		9/19 sets 8/19 sets	