

Features and Construction:

- The machine is movable, and does not require a foundation to install
- Work pieces are easily fed into and removed from the machine
- The saw tension can be read from the tension indicator
- A counter weight controls the blade tension
- Micrometric adjustment is effected by a hand wheel
- Saw guides are coated with Bakelite for high wear resistance
- Dynamically balanced upper and lower wheels ensure smooth machine running
- Bronze pieces are provided for wheel cleaning
- The machine's double cast iron support arms suit heavy-duty cutting

Automatic Features and construction:

- The feed speed is operated by a hydraulic system, which makes the machine suitable for cutting a range of lumber types
- Feed roller movement is actuated by a combination air and hydraulic system
- The feed rollers can be switched to an automatic or semi-automatic status, This saves time when working with different types of lumber
- The powered elevation of the upper wheel makes blade replacement easy (TF-900 only). A hand wheel is provided for micrometric adjustment

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



- The table gives adequate space for convenient in feed and out feed for resaving
- The auxiliary table rollers are easy and convenient to use



- The machine is movable, and does not require a foundation to install
- The heavy-duty lower wheel is dynamically balanced for smooth running
- The saw wheels run on precision bearings



- The fence is heavily constructed for high stability
- Fence adjustment is fast and simple