



Specification

ITEM	MODEL	SS-160E 1,600mm	SS-160E 2,200mm
Sliding table dimension		1,600 x 315 mm	2,200x360 mm
Cast iron table		548 x 896 mm	548 x 896 mm
Extension table (rear)		455 x 446 mm	455 x 446 mm
Extension table (front)		320 x 830 mm	320 x 830 mm
Table size		1,003x1,726 mm	1,003x1,726 mm
Round rail		Φ40	Φ40
Main saw blade (max.)		305mm(355)	305mm(355)
Main saw bore		30mm	30mm
Max. cutting height with blade 305 mm at 90 ° (355 mm)		90mm (115mm)	90mm (115mm)
Max. cutting height with blade 305 mm at 45 ° (355 mm)		62 mm (70 mm)	62 mm (70 mm)
Main motor power (3 ph)		5HP (3.75kw)	5HP (3.75kw)
Main blade speed		4.000 r.p.m	4.000 r.p.m
Scoring saw blade		120 mm	120 mm
Scoring saw blade bore		20 mm	20 mm
Scoring blade motor power (optional)		¼ HP (0.56 kw)	¼ HP (0.56 kw)
Scoring blade speed		8.000 r.p.m	8.000 r.p.m
Cutting width		835mm (1,250 mm optional)	835mm (1,250 mm optional)
Main saw blade tilting adjustment		Manual (0° ~45°)	Manual (0° ~45°)
Saw guard		Simple (overhead guard optional)	Simple (overhead guard optional)
Dust collection system		120 mm / 60 mm	120 mm / 60 mm
N.W./G.W./MEAS. (machine)		410/510 kgs (1,400x1,135x1,060 mm)	410/510 kgs (1,400x1,135x1,060 mm)
N.W./G.W./MEAS. (sliding table)		60/66 kgs (1,700x470x240 mm)	79/84 kgs (2,300x470x240 mm)
N.W./G.W./MEAS. (overhead guard)		39/40 kgs (1,420x980x120 mm)+ ½ kgs (640x210x210mm)	
Ctn Q'ty:		16/32 sets	16/32 sets

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!