



■JPA1070T40/T60 ■JPA1075T80/T100
Vertical Baler Double-cylinder Series

PRODUCTS

SPECIFICATION

This machine uses the hydraulic drive, with double-cylinder ,durable and powerful.

It uses the button to control which can realize many kinds of operation mode, the packing height can be adjusted according to the material size.

Special feed opening and automatic out package of equipment,the operation is simple, the feed opening install the stroke interlocking device which will be safe and reliable.

Pressure force, bale size can be designed according to customer's requirements.



MACHINE PARAMETER

Model	Hydraulic Power (Ton)	Bale Size (L*W*H mm)	Feed Opening Size (L*H mm)	Chamber Size (L*W*H mm)	Output (Bales/hr)	Voltage (customizable) (V/HZ)	Power (kw/hp)	Machine Size (L*W*H mm)	Machine Weight (kg)
JPA1070T40	40	1100*700*(500-900)	1100*500	1100*700*1450	6-12	380V/50HZ	5.5kw/7.5hp	1600*1100*3150	1800
JPA1070T60	60	1100*700*(500-900)	1100*500	1100*700*1450	5-8	380V/50HZ	7.5kw/10hp	1600*1100*3250	2200
JPA1075T80	80	1100*750*(500-900)	1100*500	1100*750*1500	4-6	380V/50HZ	11kw/15hp	1650*1200*3250	2600
JPA1075T100	100	1100*750*(500-900)	1100*500	1100*750*1500	4-6	380V/50HZ	15kw/20hp	1650*1200*3250	3200

SAMPLE OF MACHINE



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!