



NR-1050 / 2



Fixed-portal CNC Working Center NR-1050

Versatile configuration makes the NR series the ideal solution for all machining needs.



NR-1050 / 4

Mass production of complex parts.

Engineered and built with the structural integrity to withstand the most demanding of applications.

SPECIFICATIONS

Model	NR-1050	NR-1050 / 2	NR-1050 / 4
Dimensions of working table	3000 x 1500mm	3000 x 1500mm	3000 x 1500mm
X-, Y-, Z-axis travel	3000/1600/250mm	3500/1600/250mm	3500/1600/250mm
X-, Y-, Z-axis max. positioning speed	45/45/15m/min	45/45/15m/min	45/45/15m/min
Machining unit:	ISO30 ATC routing spindle	ISO30 ATC routing spindle	Manual-collet routing spindle
	Motor: 7.5-15hp Rotation speed: 1200-18000rpm Capacity of tool magazine: 8 pcs	Motor: 7.5-15hp x 2 Rotation speed: 1200-18000rpm Capacity of tool magazine: 8 pcs x 2	Motor: 7.5-15hp x 4 Rotation speed: 1200-18000rpm
Capacity of vacuum pump	250m ³ /hr (50Hz, 7.5hp)	250m ³ /hr (50Hz, 7.5hp)	250m ³ /hr (50Hz, 7.5hp)
Machine dimensions:	Floor area: 4740 x 3100mm Height: 2300mm Weight: 5000kgs	Floor area: 5800 x 3100mm Height: 2560mm Weight: 6000kgs	Floor area: 5800 x 3100mm Height: 2560mm Weight: 7500kgs

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

PT. Valtekindo Global Intertek

HO-20