



EFFICIENCY AND ECONOMY

DESIGN FEATURE

- * Pneumatic and easy changeable spindle unit
- * 6 depth stop of adjustment
- * Mechanical brake
- * Air blowpipe
- * Two speed 10,000/20,000 rpm of spindle
- * Convenient air pedal control unit

STANDARD EQUIPMENT

- * Flat belt: 1 pc
- * Table guide fence
- * Collect: $\frac{1}{4}$ " , $\frac{1}{2}$ "
- * Router bit: $\frac{3}{8}$ "
- * Guide pin: $\frac{3}{16}$ "- $\frac{1}{4}$ " , $\frac{5}{16}$ "- $\frac{3}{8}$ " , $\frac{7}{16}$ "- $\frac{1}{2}$ "
- * Plastic dust cover
- * Grease gun
- * Wrenches and hexagon keys
- * Tilting table
- * Hydraulic stabilizer control spindle

SPECIFICATION

MODEL		HR5	HR7
Throat clearance	(mm)	500	650
Spindle speed	(r.p.m.)	10000/20000	10000/20000
Spindle motor	(HP)	3	5
Vertical stroke of spindle	(mm)	100	100
Clearance between chuck and table	(mm)	150	300
Depth end stops		6	6
Table size	(mm)	610×460	750×600
Overall dimensions	(mm)	900×610×1730	1100×800×1600
Packing size	(mm)	1060×710×1150	1400×900×1800
N.W./G.W.	(kgs)	280/350	500/650

* All specifications, dimensions and design characteristics shown in this catalogue are subject to change without notice.

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



HR5 Overarm Router Table can be tilted to 45° and extended up to 1010×660mm (on request)



HR 7