

Manual & CNC Routers



HR-5

HR-7



HR-750

High Speed Router (manual)

MODEL	HR-5	HR-7	HR-750
Throat clearance	500 mm.	650 mm.	750 mm.
Spindle speed	10,000 / 20,000 r.p.m.	10,000 / 20,000 r.p.m.	10,000 / 20,000 r.p.m.
Spindle motor	3 HP	5 HP	5 HP (7 1/2 HP optional)
Vertical stroke of spindle	100 mm.	100 mm.	100 mm.
Clearance between chuck and table	150 mm.	300 mm.	285 mm.
Depth end stops	6	6	6
Table size	610 x 460 mm.	750 x 600 mm.	905 x 765 mm.
Packing dimensions	1,060 x 710 x 1,150 mm.	1,400 x 900 x 1,800 mm.	1,055 x 1,530 x 1,830 mm.
N.W. / G.W.	280 / 350 kgs.	500 / 650 kgs.	650 / 800 kgs.



PBP-2412AB (9V3H1S)
Pointek CNC Point to Point Machine

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

CNC Router

MODEL		PBP-2412AB (9V3H1S)	PBP-3012AB (9V3H1S)
Table	Vacuum plates table Vacuum pad Working area	L=1,200 mm. 4 tables 2 square pads / each table 2,400 x 1,200 mm.	L=1,200 mm. 6 tables 2 square pads / each table 3,000 x 1,200 mm.
Max. working stroke	X axis Y axis Z axis Spindle elevation Working height Vacuum zone	2,600 mm. 1,600 mm. 250 mm. 150 mm. 150 mm. Two Zones	3,200 mm. 1,600 mm. 250 mm. 150 mm. 150 mm. Two Zones
Rapid speed	X,Y axis Z axis Spindle speed Spindle type Spindle power Vacuum pump power CNC Controller Pneumatic boring head	80 M/min. 20 M/min. 1,000-24,000 r.p.m. ATC Air cooling (HSD) 8 KW (11 HP) 3.75 KW (5 HP)-100 m3/h OSAI-XP+PC 9V3H1S	80 M/min. 20 M/min. 1,000-24,000 r.p.m. ATC Air cooling (HSD) 8 KW (11 HP) 3.75 KW (5 HP)-100 m3/h OSAI-XP+PC 9V3H1S