



# GF-506U

## Double Side Curved Sander

- With variable speed of sanding belt and feeding, suitable for different stock material and even sealer sanding.
- Patent design for long terms mass production
- Sanding stock of chair post-etc, pieces thickness can be different from the front to end
- Sanding direction just follow the word grain so you can get the best sanding result
- Switch for sanding forward or reversely to get the best effect in work piece.



GF-506U Working Sample



### Specification

|                                           |                       |
|-------------------------------------------|-----------------------|
| Model                                     | GF-506U               |
| SANDING BELT DRIVEN MOTOR                 | 1.5 HP x2             |
| SANDING BELT SPEED                        | 0~565 M/min           |
| SANDING BELT SIZE                         | 152 x 635m/m          |
| FEEDING DRUM SIZE                         | 100Ø x 152 m/m        |
| FEEDING MOTOR                             | ¼ HP x 4              |
| FEEDING SPEED (infinitely variable speed) | 0~21m/min             |
| FEEDING ROLLER SIZE                       | 75Ø x 75m/m           |
| FEEDING ROLLER NUMBER                     | 4 PCS                 |
| WORKING THICKNESS                         | 15 ~75 m/m            |
| WORKING HEIGHT                            | 25~75m/m              |
| WORKING LENGTH                            | 220~1500m/m           |
| MACHINE SIZE                              | 1350 x 720 x 1240 m/m |
| PACKING SIZE                              | 1450 x 820 x 1440 m/m |
| M.W/G.W                                   | 570/680 KGS           |

**Note :**

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

\* Specification and design characteristics are subject to change without prior notice.