



GF-506N.512N

Double Side Curved Sander

- With infinitely variable speed of sanding belt and feeding, suitable for different stock material and even sealer sanding
- Choose standard 6"L (GF-506N) or larger 12"L(GF-512N) belt drum
- Patent design for long terms mass production.
- Sanding stocks or chair back, arm ... etc
- Switch for sanding forward or reversely to get the best effect in work piece



GF-506N Working Sample



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Specification

MODEL	GF-506	GF-512N
SANDING BELT DRIVEN MOTOR	2 HP x 2	2 HP x 2
SANDING BELT SPEED (infinitely variable speed)	0~980 M/min	0~980 M/min
SANDING BELT SIZE	152 x 850 m/m	305 x 850 m/m
SANDING DRUM SIZE	175 Ø X 152 m/mm	175 Ø x 305 m/mm
SANDING BELT OSZILLATION MOTOR	1/8 HP	1/8 HP
SANDING BELT OSZILLATION RANGE	100 m/m	100 m/m
FEEDING MOTOR	¼ HP X 4	¼ HP X 4
FEEDING SPEED (infinitely variable speed)	0 ~ 28 M/min	0 ~ 28 M/min
FEED ROLLER SIZE	100 Ø x 50m/m	100 Ø x 50m/m
FEEDING ROLLER NUMBER	8 PCS	12 PCS
WORKING THICKNESS	6 ~ 100 m/m	6 ~ 100 m/m
WORKING HEIGHT	25 ~ 150m/m	25~300m/m
WORKING LENGTH	400~1500 m/m	400~1500 m/m
MACHINE SIZE	1050 x 1100 x 1000 m/mm	1050 x 1100 x 1500m/mm
PACKING SIZE	SIZE 1150 x 1200 x 1200 m/m	1150 x 1200 x 1350m/m
N.W/G.W	480/530 KGS	510/600 KGS