



PRY-F Series Semi-automatic Flute Laminator

Features

1. Turn up bridge plate is convenient for cleaning; discontinuous water-circulating system ensures washing clean.
 2. Automatic feeding for bottom sheet, manual feeding for top sheet (feeding from side for top sheet is optional).
 3. Flexible front register and bottom sheet does not exceeds the top sheet.
 4. It's adjustable for the front-and-rear lamination between bottom sheet and top sheet
 5. The paperboard of bottom sheet can be more than 300gsm, A/B/C/D corrugated cardboard.
 6. Movable lengthened pressing section is optional for corrugated board thicker than B flute, and its length is more than 800mm
- ※Optional: PLC integrated program module control1.

Technical data

Model	PRY-1000F	PRY-1300F	PRY-1450F	PRY-1600F
Max paper size	1000×1100mm	1300×1100mm	1450×1100mm	1600×1100mm
Min paper size	320×450mm	320×450mm	320×450mm	320×450mm
Total electric consumption	7kw	7kw	7kw	11kw
Speed	0-90m/min	0-90m/min	0-90m/min	0-90m/min
Weight	3.2t	4.2t	4.8t	5.5t
Overall Dimensions(mm)	7400×1530×1400	7400×1830×1400	7400×2080×1400	7400×2250×1400



Side feeding



Top sheets section



Bottom sheets section

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!