



Specification

MODEL	25R	25K	37R	37K	25RK	37RK
Working width mm (inch)	609 (24")	609 (24")	914 (36")	914 (36")	609 (24")	914 (36")
Working height mm (inch)	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")
Main motor standard HP	15	10	20	15	15,10	20,15
Maximum HP	20	20	20	20	20,15	20,15
Feed motor HP (KW)	2(1,49)	2(1,49)	2(1,49)	2(1,49)	2(1,49)	3 (2,24)
Power rise and fail HP	½	½	½	½	½	½
Feed speeds (variable) m/mm (ft/min)	6-26 (19-85)	6-26 (19-85)	6-26 (19-85)	6-26 (19-85)	6-26 (19-85)	6-26 (19-85)
Standing belt dimension mm (inch)	635 x 1905 (25" x 75")	635 x 1905 (25" x 75")	939 x 1905 (37"x75")	939 x 1905 (37"x75")	635 x 1905 (25" x 75")	939 x 1905 (37"x75")
Compressed air required at 5 atoms (CFM)	6	6	6	6	7	7
Exhaust volume requirement M ³ /HR (CFM)	1030 (600)	1030 (600)	1720(1000)	1720(1000)	2064 (1200)	3500 (2000)
N.W. Kgs	1200	1200	1440	1440	2000	3200
G.W. Kgs	1500	1500	1850	1850	2450	3650
Dimensions : Length mm (inch)	1117 (44")	1117 (44")	1422 (56")	1422 (56")	1930 (76")	1930 (76")
Dimensions : Width mm (inch)	1422 (56")	1422 (56")	1524 (60")	1524 (60")	1701 (67")	1905 (75")
Dimensions : Height mm (inch)	2057 (81")	2057 (81")	2057 (81")	2057 (81")	2057 (81")	2057 (81")
Packing size mm	165 x 150x 216	165 x 150x 216	173 x 157 x 221	173 x 157 x 221	208 x 185 x 213	218 x 185 x 216

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!