



Specification

MODEL	43R	43K	52R	52K	43RK	52RK	43RRK	52RRK	43RKK	52RKK
Working width mm (inch)	1067("42)	1067("42)	1270("50)	1270("50)	1067("42)	1270("50)	1067("42)	1270("50)	1067("42)	1270("50)
Working height mm (inch)	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")	127 (5")
Main motor standard HP	30(40)	20(30)	30(50)	20(30)	30,20 (40,25)	30,20 (50,30)	40,20,30	40,20,30	40,20,30	40,30,20
Feed motor HP (KW)	3	3	3	3	3	5	5	7 1/2	5	7 1/2
Power rise and falls HP	1/2	1/2	1/2	1/2	1/2	1	1	1	1	1
Feed speeds (variable) m/min	6-26	6-26	6-26	6-26	6-26	6-26	6-26	6-26	6-26	6-26
Standing belt dimension mm (inch)	1092 x 2134 (43' x 84')	1092 x 2134 (43' x 84')	1320 x 2134 (52' x 84')	1320 x 2134 (52' x 84')	1092 x 2134 (43' x 84')	1320 x 2134 (52' x 84')	1092 x 2134 (43' x 84')	1092 x 2134 (43' x 84')	1092 x 2134 (43' x 84')	1320x2134 (52' x 84')
Compressed air required at 5 atoms (CFM)	6	6	7	7	7	7	7	7	7	7
Exhaust volume requirement M ³ /HR (CFM)	2500 (1500)	2600 (1500)	3500 (2000)	3500 (2000)	5180 (3000)	6850 (4000)	7750 (4485)	9870 (5500)	7760 (4485)	9970 (3600)
N.W. Kgs	2200	2200	2900	2900	4000	4700	4485	5060	5700	5350
G.W. Kgs	2500	2500	2800	2800	4500	5200	4850	5880	4890	5880
Dimensions : Length mm (inch)	2489(98")	2489(98")	2718(107")	2718(107")	2459(96")	2459(96")	2459(96")	2718(107")	2459(96")	2718(107")
Dimensions : Height mm (inch)	2100(75")	2100(80")	2100(75")	2100(75")	2100(80")	2100(80")	2100(80")	2100(80")	2100(80")	2100(80")
Packing size cm	259x188x225	259x188x225	227x118x228	227x118x228	259x213x226	277x226x226	228x225x226	295x226x226	288x225x225	295x226x226

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!