



Finger Assembler



Finger Assembler 15AH(4.6M) / 20AH (6.2M)

Model	15AH	20AH
Length of working table	4,600mm	6,200mm
Available length of work pieces	2,500~4,600mm	2,500~6,200mm
Available thickness of work pieces	20~80 mm	20~80 mm
Available width of work pieces	30~150mm	30~150mm
Cut off saw		
Spindle diameter	25.4 mm(1")	25.4 mm(1")
Saw diameter	304.8 mm(12")	304.8 mm(12")
Power required		
Feeder	1 HP	1 HP
Cut of saw	3 HP	3 HP
Hydraulic pump	5 HP	5 HP
feeding speed	63.8 M/min ~50 Hz, 70.2 M/min ~ 60Hz	63.8 M/min ~50 Hz, 70.2 M/min ~ 60Hz
Packing dimension	5,900x900x1,700 mm	7,400x900x1,700 mm
N.W./G.W.	2,100/2,450kgs	2,550/3,000kgs



15ACH (4.6M) / 20ACH (6.2M)

Finger Assembler with Chain Feeding

Model	15 ACH	20 ACH
Length of working table	4,600 mm	6,200 mm
Length of pre- press station & Chain feeding table	2,915 mm	2,915 mm
Available length of work piece	2,500~4,600 mm	2,500~6,200 mm
Available thickness of work piece	20~80 mm	20~80 mm
Available width of work piece	30~150 mm	30~150 mm
Cut off saw		
Spindle diameter	25.4 mm.(1")	25.4 mm.(1")
Saw diameter	304.8 mm(12")	304.8 mm(12")
Power required		
Feeder	1 HP	1 HP
Chain feeding	½ HP	½ HP
Brush wheel	¼ HP	¼ HP
Cut off saw	3 HP	3 HP
Hydraulic pump	5 HP	5 HP
Feeding speed	63.3 M/min~50 Hz, 70.2M/min~60Hz	63.3 M/min~50Hz,70.2M/min~60Hz
Packing dimensions	8,615x1,270x1,550 mm	9,315x1,270x1,550mm
N.W./G.W	2,500/2,850kgs	2,950/3,400kgs

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!