



SPECIFICATIONS 説明

Workpiece Length	160-up	Edging Thickness	0.4-6 / (13)
Workpiece Width	65-up	Feed Speed	6-25 M/min
Workpiece Thickness	10-60	Air Pressure Required	6 kg/cm ²

MODEL	EB-350	EB-400	EB-450	EB-500	EB-580	EB-660	EB-750
Feed power	1.5 kw	1.5 kw	2.3 kw	2.3 kw	3.8 kw	3.8 kw	4.0 kw
Total horsepower	7 kw (9.5 hp)	8 kw (10.5 hp)	8.5 kw (11.5 hp)	11 kw (15 hp)	13.5 kw (18 hp)	14.5 kw (19.5 hp)	18 kw (24 hp)
Net weight	1,230 kgs	1,390 kgs	1,570 kgs	1,700 kgs	2,170 kgs	2,600 kgs	3,000 kgs
Gross weight	1,530 kgs	1,740 kgs	1,970 kgs	2,150 kgs	2,670 kgs	3,200 kgs	3,750 kgs
Machine dimensions	3,700x1,800x1,450	4,220x1,800x1,450	4,650x1,800x1,450	5,200x1,800x1,450	6,100x1,800x1,450	6,800x1,800x1,450	7,700x1,800x1,450
Packing dimensions	3,570x920x1,500	4,100x920x1,500	4,520x920x1,500	5,150x920x1,500	6,000x920x1,500	6,670x920x1,500	7,570x920x1,500

The model number with "C" means that the machine equips with splash guard and increases around 200-300mm in overall length.

WORKING UNIT

END CUTTING UNIT	POWER	0.67 HP x 2
	RPM	12,000
	CUTTER	120 x 20 x 2.6
FLUSH TRIMMING UNIT	POWER	1 HP x 2 (2 HP x 2)
	RPM	12,000
	CUTTER	70 x 16 x 14.3
FINE TRIMMING UNIT	POWER	1 HP x 2 (0.67 HP x 2)
	RPM	12,000 (18,000)
	CUTTER	70 x 16 x 14.3 (or 73 x 16 x 16 R2~R5)
TOP PROFILE TRIMMING UNIT	POWER	0.5 HP x 2
	RPM	12,000 (18,000)
	CUTTER	73 x 16 x 16 (R2~R5)
BOTTOM PROFILE TRIMMING UNIT	POWER	0.5 HP x 2
	RPM	12,000 (18,000)
	CUTTER	73 x 16 x 16 (R2~R5)
BUFFING UNIT	POWER	0.5 HP
	RPM	1,720
	BUFFING	150 x 22 x 24
SCORING SAW UNIT	POWER	4 HP x 1
	RPM	7,500~9,000
	CUTTER	175~200 x 25 x 3 (3~8)
CORNER BUFFING UNIT	POWER	0.5 HP
	RPM	2,780
	BUFFING	150 x 22 x 40
EDGE SANDER UNIT	POWER	2 HP
	RPM	1,720
	SANDER	100 x 635

All specifications, designs and characteristics shown on this catalogue are subject to change without prior notice.

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!