



Specification

F-C61 HORIZONTAL FINGER SHAPER

MODEL	
range of work piece length	150~900 mm
range of work piece width	15~160 mm
range of work piece height	16~55 mm
feeding speed	max. 90 pieces / min
trimming saw speed	2800 rpm (50hz) 3400 rpm (60hz)
finger cutter speed	5000 rpm
scoring saw speed	2800 rpm (50hz) 3400 rpm (60hz)
POWER REQUIRED	
feed of chain motor	7- ½ HP
trim saw motor (and scoring saw)	10 HPx2
shaper cutter motor	20 HPx2
scoring saw motor	1 HPx3
cutter spindle diameter	Ø70 mm
Dia of cutter (in/out)	Ø 210 mm
dust hood outlet diameter	6"x2,4"x4
machine dimensions (L x H x W)	6260x1510x2550 mm

F-T67 CHAIN DRIVE PRE-RESS ASSEMBLY STAND

MODEL	6M
range of work piece height	15~100 mm
range of work piece width	25~200 mm
feeding speed	140m/min
feed drive motor	2 HP x 2
for conveyor motor	2 HP
brush wheel drive motor	½ HP
wheel driven motor	½ HP
overall length	6710 mm
overall width	1140 mm
overall height	1110 mm
packing dimensions (L x H x W)	6620x1200x1220 mm

F-A63 AUTO ASSEMBLE PRESS

MODEL	6 M
available length of product	6200 mm
available thickness of product	15~60 mm
available width of product	15~160 mm
feeding speed	80 m/min
capacity length product	5pcs
POWER REQUIRED	
feed drive motor	2 HP
max. assembly pressure	0~150 kg/cm ²
hydraulic power unit	5 HP
cut-off saw	5 HP
dust hood outlet diameter	4" (101.6mm)
machine dimension (L x H x W)	7400x1400x1380 mm
noise value	84 db
packing dimensions (L x H x W)	7500x1500x1060 mm

F-131 MANUAL FEEDING TABLE

MODEL	
conveyor table width	610 mm
feed drive motor	1 HP
machine length	2500 mm
machine width	700 mm
machine height	910 mm

F-132 AUTOMATIC WOOD ARRANGING CONVEYOR TABLE

MODEL	
conveyor table width	800 mm
feed drive motor	1 HP
brush wheel drive motor	1 HP
machine length	2510 mm
machine width	1500 mm
machine height	1600 mm



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!