


CURVED WOOD FORMING PRESSES

FORMING MOULDINGS



FEATURES:

1. This m/c is suitable for various membrane wood, solid wood made curved forming pattern and can be installed electric platen moulding to make multi-layer pressed forming, Quick of production rate.
2. This m/c can be processed in cold pressing which just shut off heating source and make flat integrated layer laminating pressing.
3. The auto temp controlling switches can be made electric heating or steam boiler heating two types.(We drill hole at forming mouldings and insert the steel tube to install the electric thermo-couple to heat the moulding for curved forming. As for the steam boiler heating, which just drill hole at forming moulding to obtain the heating medium such as steam, hot transfer oil circulation to heat the moulding for curved forming)

SINGLE DIRECTION SPECIFICATIONS

Model	Platen size(AxB)	Total thrust	Hyd. cyl.	Stroke(C)	Hyd. power
CT-33-100	910x910mm	100 Ton	φ 250x1	900mm	7-1/2HP
CT-34-100	1220x910mm	100 Ton	φ 250x1	900mm	7-1/2HP
CT-35-100	1520x910mm	100 Ton	φ 250x1	900mm	7-1/2HP
CT-36-150	2000x910mm	150 Ton	φ 180x3	900mm	7-1/2HP
CT-48-100	2500x1250mm	100 Ton	φ 125x4	900mm	7-1/2HP
CT-35-3	1520x1000mm	100 Ton(Main)	φ 250x1(Main)	900mm(Main)	7-1/2HP
		70 Ton(Side)	φ 150x2(Side)	240mm(Side)	

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!