

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Biomass Boiler

Widely used in high-grade residential, hotel, restaurant, sauna bath center, Leisure clubs, villas, factories, schools, and institutions, with hot water bath. Heating and drying.

型号 (Model)	热功率 (Kcal/H)	热效率 (%)	取暖面积 (m ²)	热水量 (温差40℃) (t/h)	耗燃料 (kg/h)	使用燃料
CLHG0.058-M	5x10 ⁴	≥90	400-500	1-1.25	10-12	φ6-8生物质颗粒
CLHG0.12-M	10x10 ⁴	≥90	700-1000	2-2.5	20-25	φ6-8生物质颗粒
CLHG0.23-M	20x10 ⁴	≥90	1500-2000	4.5-5	45-50	φ6-8生物质颗粒
CLHG0.35-M	30x10 ⁴	≥90	2500-3000	7-7.5	70-75	φ6-8生物质颗粒
CLHG0.40-M	40x10 ⁴	≥90	3000-3500	9-10	100	φ6-8生物质颗粒
CLHG0.58-M	50x10 ⁴	≥90	4000-5000	10-12.5	110-125	φ6-8生物质颗粒
CLHG0.70-M	60x10 ⁴	≥90	5000-6000	12-15	130-150	φ6-8生物质颗粒
CLHG0.93-M	80x10 ⁴	≥90	6500-7500	17-20	180-200	φ6-8生物质颗粒
CLHG1-M	100x10 ⁴	≥90	9000-10000	20-23	250	φ6-8生物质颗粒
CLHG1.2-M	120x10 ⁴	≥90	10500-11500	24-27	300	φ6-8生物质颗粒