



SSHJ Series Dual-shaft Oar Efficient Mixer

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

- The operation speed is low; the blending efficiency is high; the action is gentle; various liquids can be added
- Mixing time is short (40 second-60 seconds/batch), the degree of homogeneity is high ($cv < 5\%$).
- Full-length open door structure, no material leakage, discharging speed is fast, no residual.
- It is applicable to industries such as premix, chemical, medicine, energy environment protection, etc.

型号 Model	产量 (M ³ /Batch)	功率 Power(KW)	有效容积 (L) usefull volume	均匀度 (CV<%) Homogeneity degree	混合时间 (S)Mixing period of the machine	重量 (T)	尺寸 (MM)
SSHJ100	0.20m ³ /批	3	0.2	<5%	40-90	0.62	1500X1200X1200
SSHJ250	0.50m ³ /批	5.5	0.5			1	1720X1500X1360
SSHJ500	1m ³ /批	11	1			1.7	2360X1900X2050
SSHJ1000	2m ³ /批	22	2			2.8	2700X2100X2400
SSHJ2000	4m ³ /批	30	1			1.6	2950X2500X2500
SSHJ3000	6m ³ /批	37	6			6.5	3500X2800X2600
SSHJ5000	10m ³ /批	45	10			9.8	4500X3200X2800



SHJ Series Single-Shaft Twin Screw Mixer

SSHJ

Dual-shaft Oar Efficient Mixer

- The degree of homogeneity is high $CV < 5-7\%$
- Mixing time: 3-6 minutes
- Discharge structure: manual, electric or pneumatic.
- It is applicable to industries such as energy environment protection, chemical, feed food and medicine plants etc.



型号 model	产量 (M ³ /Batch)	功率 (kw)	均匀度 (CV<%)	混合时间 time(m)	重量 (t)	尺寸 (mm)
SHJ100	0.20m ³ /批	3	<5-7%	3-6	0.35	1400X590X750
SHJ250	0.50m ³ /批	5.5			0.75	1860X805X900
SHJ500	1m ³ /批	7.5			1.2	2100X1050X1200
SHJ1000	2m ³ /批	18.5			2.1	2500X1630X1800
SHJ2000	4m ³ /批	22			3.5	2800X1800X2600
SHJ3000	6m ³ /批	30			4.2	3200X1900X2100
SHJ5000	5m ³ /批	37			6.3	4600X2100X2300

SHJ

Single-shaft Twin Screw Mixer