



DIE CUTTING & CREASING MACHINE

No. 0309

ZX1600/1800/1200

Creasing and Cutting Machine



No. 0307

ZX1300/1400

Creasing and Cutting Machine



No. 0308

ZX750/203C/1100/1200

Creasing and Cutting Machine



No. 0309

ZX750/203C/1100/1200

Creasing and Cutting Machine



No. 0310

ZX750/203C/1100/1200

Creasing and Cutting Machine



No. 0311

ZX750/203C/1100/1200

Creasing and Cutting Machine



DESCRIPTION

1. It's special equipment for creasing and cutting ordinary cardboard corrugated board plastic and leather in general, applicable to printing packaging decoration and plastic industries.
2. It's characterized by compact structure, fine workmanship, big pressure, high precision and easy and reliable operation, etc.

Specifications

Model	Inner Chase	Max. rule length	Speed (strokes/min)	Motor power	Weight	Dimensions (mm)
ZX750	750x520mm	<15m	25±2	2.2kw-4H	2000kg	1450x1600x1450
ZX203C	930x670mm	<25m	23±2	4kw-4H	3000kg	1650x1880x1700
ZX1100	1100x800mm	<32m	20±2	4kw-6H	4500kg	1950x2150x1850
ZX1200	1200x820mm	<35m	20±2	4kw-6H	5000kg	2050x2150x1900
ZX1300	1300x920mm	<40m	16±2	5.5kw-6H	6200kg	2350x2100x1950
ZX1400	1400x1000mm	<45m	15±2	5.5kw-6H	6800kg	2450x2100x2000
ZX1600	1600x1250mm	<50m	13±2	11kw-6H	12000kg	2780x2300x2400
ZX1800	1800x1300mm	<60m	13±2	11kw-6H	14000kg	2980x2300x2400
ZX2000	2000x1400mm	<65m	13±2	15kw-6H	16000kg	3180x2400x2580
ZX2200	2200x1400mm	<70m	13±2	15kw-6H	18000kg	3380x2400x2580
ZX2500	2500x1500mm	<80m	11±3	22kw-6H	20000kg	3680x2500x2580

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

No. 0312

ZXDN300 Laser Cutting Machine

Specifications

Working area	1100x800mm
Drive style	Double direction import precision ball screw transmission
Surrounding degrees	5°C-35°C
Cooling water degrees	5°C-30°C
Cooling water	pure water
Protection gas	non-oil air with drying
Relatively humidity	≤80%
Supply power	Single phase 220V±5% 50Hz 10A
Cutting speed	0-3000mm/min setting software
Cutting precision	≤0.05mm
Rep-site precision	≤0.02mm
Operation control	LCD, EN & Chinese operation menu,

DESCRIPTION

Fixed light road (laser head fixed, The cutting materials motion) Double directions transmission by the imported accuracy ball screw shafts (more accuracy), the die board's tolerance is 0.05mm Once time can cut 18-22mm, the cutting seam will be vertical and even; cutting one meter is about 2 minutes, one cutting die-board of 8-makeup patterns box only need half hour.

Applicable process material: Acrylics plastic products 6-9-15-18-22MM, leathers and cartons, etc non-metal material
Transmission port: Contact USB, equip high stored program and could be working offline
Instruction system: International standard, compatible CDR, CAD etc various software
Control software: Jialuo laser cutting & Engrave control system (En & Chinese version)

