

Vibrating Screener

Brief Introduction:

YSKF series vibrating screener makes use of horizontal vibrating motor as vibration power, the material is tossed in the screen, meanwhile, put raw materials forward in a straight line, so called vibrating screener, Materials from the feeder machine evenly into the feeding inlet of vibrating screener, materials are discharged from their respective outlet through multi-screen, producing a different kinds of materials. With low energy consumption, high output, simple structure, easy maintenance, fully enclosed structure, no dust, automatic discharging, more suitable for pipeline operations.



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

型号 (Model)	产量 (t/h)	功率 (kw)	激震力 (kg)	震动频率 (batch/min)	筛理面积 (mm)
YSKFZ60*2C	1-2	0.25*2	3000	920	1000*600
YSKFZ80*2C	2-4	0.25*2	5000	920	1500*800
YSKFZ100*2C	3-6	0.37*2	6000	920	1500*1000
YSKFZ120*2C	5-8	0.37*2	6000	920	1800*1000
YSKFZ150*2C	8-12	0.55*2	8000	920	2800*1200

Rotary Screener



Rotary screener mainly makes up with motor, reducer, roller device, frame, sealing cover, inlet and outlet. The roller device is tilted on the frame. The motor is connected with roller device through shaft coupling by the reducer, and drive roller device around its axis of rotation. When the materials fed in the roller device, due to tilt and rotation of roller device, the material on the screen surface roll and rotate. Finally the qualified materials will be discharged through the discharge port at the bottom of roller, the unqualified materials will be discharged through the discharge port at the end of the roller device. Due to the material flip and scroll, the material stuck in screener will be pop up, to the prevent the mesh plug.

型号 (Model)	产量 (t/h)	尺寸 (mm)	功率 (kw)
YGTS80x1.5	0.5-1	2150x1200x1200	1.1
YGTS100x2	1-2	2800x1300x1460	1.5
YGTS130x3	1.5-4	4420x1500x3800	2.2
YGTS150x4	3-5	5160x1700x4400	3
YGTS180x5	5-10	6300x2200x2600	4
YGTS200x6	8-12	7000x2500x5000	5.5