



PAPER CUTTING MACHINE

No. 0208

QZYK-8 Program Control Paper Cutting Machine



No. 0209

QZYK1150D-1 Program Control Paper Cutting Machine



Specification											
Model	Unit	QZX-1620BD	QZYK-1370D	QZYK-1300D	QZX-1300CD	QZYK-1150D	QZYK-920D	QZX780D	QZX203D	920C	QZYK-660
Max. Cutting Width	cm/inch	162/63.8	137/53.9	130/51.2	130/51.2	115/45.3	92/36.2	78/30.7	92/36.2	92/36.2	66/26
Max. Cutting Length	cm/inch	165/65.0	145/57.1	135/53.1	135/53.1	166/45.7	100/39.3	78/30.7	100/39.3	100/39.3	66/26
Max. Cutting Height	cm/inch	13/5.1	16.5/6.5	16.5/6.5	13/5.1	16.5/6.5	13/5.1	12/4.7	12/4.7	12/4.7	8/3.1
Main Motor Power	kw	5.5	4	4	4	4	3	3	3	3	2.2
Net Weight	kg	5500	4500	4300	3700	4000	2600	1800	2100	2100	650
Width of Machine	With sideway	cm	296	289	282	267	217	195	192	215	100
	Without sideway	cm	301	259	252	248	237	202	190	173	100
Length	cm	315	290	280	280	261	213	183	213	213	150
Height	cm	171	171	166	157	165	151	151	146	146	135
Front table length	cm	73	75	73	73	73	60	60	60	60	50
Table height	cm	93	93	93	89	89	89	89	89	89	83
Clamp Pressure	Min.	N	200	200	200	200	200	200	200	200	100
	Max.	N	55000	45000	40000	40000	30000	30000	30000	30000	8000
Knife Thickness	cm	183x12.7x1.27	160x16x1.37	152x12.7x1.27	152x12.7x1.27	139x16x1.37	110x12.7x1.27	95x12.7x1.27	110x12.7x1.27	110x12.7x1.27	76x10x1
Grinding reserve	cm	3	6	3	3	6	3	3	3	3	2.5
Smallest Cut	Without false clamp	cm/inch	3.5/1.4	3/1.2	3/1.2	3/1.2	2.5/1.0	2/0.8	2.5/1.0	2.5/1.0	2.5
	With false clamp	cm/inch	11/4.3	10/3.9	10/3.9	10/3.9	10/3.9	9/3.5	10/3.9	10/3.9	2.5
Cutting speed	cycles/min	35	45	45	45	45	45	45	30	45	40
Packing size (LxWxH)	cm	337x157x220	302x157x200	287x157x200	287x157x194	260x157x200	224x137x185	215x137x185	224x122x275	224x137x175	165x110x160
Voltage (3Phase)	v	365-395	365-395	365-395	365-395	365-395	365-395	365-395	365-395	365-395	220
Wire size	mm	4	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	4

QZZX660W Microcomputer hydraulic Paper Cutting Machine



No. 0210



No. 0210

Specifications			
Model		QZZX-660W	QZZX-660
Max. cutting width	cm	66	66
Max. cutting length	cm	66	66
Max. cutting height	cm	8	8
Max. clamping pressure	N	8000	8000
Cutting speed	cycles/min	40	40
Sending paper motor power	kw	2.2	2.2
Cutting motor power	kw	0.12	0.12
Net weight	kg	650	650
External dimension	cm	150x100x135	150x100x135
Packing dimension	cm	165x110x160	-

STRUCTURE FEATURES

The paper cutting machine has feature as automatic paper clamp, paper cut and paper send, high cut precision, low noise, and long life usage. Its design structure is easy to operate and insure safety. Its paper sending system adopts whole body spotless chrome worktable, linear guide and high-speed ball screw, so it can insure the correct position with a high speed. Both of the paper clamping device and paper clamp device adopt hydraulic driven. The pressure is adjusted stepless. The big pressure adjusting range insure various paper cutting pressure needs. It is equipped with photo cell, double hands cutting button, knife light line, knife seat jogging devices. Therefore, it can insure the operator's safety and convenient operation, high cutting precision, low noise, and long life using. This machine is suitable to cut Carbonless Paper, art paper, gray paperboard, etc. It is suitable for the workshop, school, advertisement agent, and company, etc. This machine has passed CE safety and the hydraulic system is also passed European safety standard. Microcomputer, hydraulic, encocomic

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!