

Multiple Blade Saw MBS1300-XD4



The spindle is bottom saw with lifting and a fully-enclosed protective cover: The digital or manual lifting of spindle and upper pressing frame can be optional. Strengthened type spindle and axle bed. Anti-bouncing protector for plate (Patented Product) is available.

Due to keeping innovation the specification and Machine pictures or color are subject to alteration without notice!

Application : It is used for cutting of density board, composite board solid wood boards and other large boards or grooving on surface of boards in different depths. (Door frame boards, photo frames, decorative streak and so on).



Technical Parameter			
Width of Processed material	(mm) Max. 1220: Min. 200	Power of Feeding Motor (kw)	1.5 (Optional to 3)
Thickness of Processed Roughcast (mm)	Max. 60: Min: 5	Total Power of Installed Motor (kw)	20 (Optional to 40)
Min. Processing Length (mm)	600	Feeding Speed (m/min)	0-12
Spindle Diameter (mm)	90	Pair Number / Number of Feeding Roller	8/16
Spindle Speed (r/min)	2600	Outer Diameter of Scrap Pipe (mm)	150
Saw Blade Diameter (mm)	270	Overall Dimensions (mm)	2900 x 1800 x 1400
Max. Number of Saw Blades (pcs)	60	Weight (kg)	2800
Power of Spindle motor (kw)	18.5 (Optional 37)		