



Band Saw HB-500R, HB-600R, HB-700R




- Convenient side guide adjustment is made by a micrometric adjustment knob for use with narrow blades.

Rubber laminated saw wheel

The saw wheels on models HB-500R, 600R and 700R are laminated with rubber for

WORKING EXAMPLES



Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

Specification

Model	HB-500R	HB-600R	HB-700R
Saw wheel diameter	500 mm	600 mm	700 mm
Table size	680 x 520 mm	800 x 605 mm	1000 x 700 mm
Cutting capacity	Height Width	300 x 475 mm	350 x 580 mm
		420 x 678 mm	
Width of wheel	35 mm	35 mm	40 mm
Wheel speed	720 RPM	710 RPM	600 RPM
Blade length	3999 mm	4484 mm	5151 mm
Motor	2 HP (3 HP)	3 HP (5 HP)	5 HP (7.5 HP)
Net weight	280 kg	315 kg	450 kg
Gross weight	350 kg	450 kg	600 kg
Machine size (L x W x H)	970 x 700 x 1880 mm	1060 x 800 x 2070 mm	1330 x 900 x 2290 mm
Packing size (L x W x H)	1970 x 580 x 1010 mm	2160 x 630 x 1100 mm	2380 x 650 x 1210 mm



PT. Valtekindo Global Intertek

HO-09