



HWR-300



MODEL	HWR-300
MAXIMUM CUTTING CAPACITY (W x H)	12" x 12" (300 x 300 mm)
MINIMUM CUT PIECE	2 mm
SAW WHEEL DIAMETER	24" x 2 (600 mm x 2)
SAWBLADE LENGTH	183-7/8" ~ 184-1/4" (4670 ~ 4680 mm)
SAWBLADE WIDTH	1-1/4" (32 mm)
SAWBLADE SPEED	6000 FPM
CONVEYOR BELT SIZES (W x L)	10-5/8" x 165-1/2" (270 x 4200 mm)
FEED SPEED (VARIABLE)	0~40 m/min
FEED CONVEYOR TILT	0° ~ 30°
CONVEYOR HEIGHT FROM FLOOR	40" (1016 mm)
SAW WHEEL MOTOR	20 HP
BLADE LIFT MOTOR	1/2 HP
DUST HOOD OUTLET DIAMETER	Ø4"
MACHINE DIMENSIONS (L x W x H)	88" x 85-3/4" x 74" (2235 x 2180 x 1880 mm)
PACKING DIMENSIONS (L x w x H)	90-1/2" x 88" x 80" (2300 x 2235 x 2032 mm)
NET WEIGHT	1200 kgs
GROSS WEIGHT	1400 kgs

PT. Valtekindo Global Intertek

Pressure Roller for Slicing Unit (Model No. HWR-300A)

Minimum Wood Thickness: 2mm.

Accuracy Up ideal for Composite Parquet Max. height of in feed: 200 mm.

BLADE TENSION & TRACKING

- Blade tensions is adjust by means of a hand wheel. A tension scale allows the operator to correctly adjust the tension for different kinds of blades.
- Blade tracking is adjust by turning a hand wheel.

CONVENIENT CONTROL

- The digital readout assures high accuracy cutting and convenient thickness control.
- Variable feed speed is controlled by a frequency inverter and displayed on the control panel.
- All electric controls are centralized on a control panel for operational convenience.

MOVABLE CONTROL UNIT

STANDARD EQUIPMENT

20 HP saw wheel motor
Blade lift digital control
Frequency inverter controlled conveyor feed
Feed conveyor tilt 0~30
One 1-1/4" saw blade
Tool box with service tools

OPTIONAL EQUIPMENT

Inverter for 20 HP saw wheel motor
Pressure rollers for slicing unit

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

HO-17