



GANG RIP SAW



GRS-300A

The fast way to gain superior straight accuracy for gang rip sawing from HOLYTEX, the quality -built GRS-300a delivers unparalleled accuracy, stability and rigidity. capable of ripping short pieces of wood to 2430 mm of length. powerful 30 HP motor drive (or optional 50 HP) comprehensive CE safely guards.....and many more fine features

Specifications

MODEL	GRS-300A	GRS-300A/CE
maximum working width & thickness	300x125 mm	300x125 mm
maximum saw dia.	Ø405 mm	Ø405 mm
spindle dia./ key groove	Ø70/10 mm	Ø70 / 10 mm
variable feeding speed	6-34m/mm	6-4 m/min
spindle speed	3600 rpm	3600 rpm
minimum working length	230 mm	230 mm
spindle motor	30 (40,50) Hp	30 (40,50) Hp
feeding motor	3(5) HP	3 HP (frequency inverter control
elevation motor	¼ HP	¼ HP
spindle hoist motor	¼ HP	¼ HP
N.W/G.W.	1300/1500 kgs	2000/2200 kgs
machine dimensions	2250x1250x1500 mm	2600x1450x1700 mm
packing dimension	2350x1350x1650 mm	2700x1500x1850 mm

A quality proven gang rip saw enable high productivity plus precision ripping

- excellent for ripping wood panels, fumiture board, building material, decoration materi, acrylic board and light metallic board, etc
- saw spindle beneath table facilitates dust handing
- precise spindle provides high accuracy operation
- 2 step pressure control for feed roller
- the machine frame is manufactured from FC-30 cast from for maximum rigidity and stability
- variable feed speeds suit all types of wood material, max , feeding speed to 34m/min
- the spindle elevation is driven by an independent motor for convenient adjustment of spindle
- max. cutting thickness to 125 mm

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!