



Specification

STRAIGHT LINE RIP SAW

MODEL	HR-12	HR-16	HR-18/HR-20
Gluing length range (mm)	200-1800	200-2500	300-3200
Max. depth of cut (mm)	75	75	120/135
Max. saw blade diameter	355	355	460/510
Supplied saw blade specification	D350T70B5	D350T70B5	D350T70B5
Saw bore(mm)	50.8	50.8	50.8
Saw arbor motor (HP)	10(15)	10(15)	15(20)
Feed drive motor (HP)	1.5	1.5	2(3)
Feed speed (60Hz) (m/min)	11-32 variable speed	11-32 variable speed	13-50 variable speed
Saw arbor brake system	Standard	Standard	Standard
Height of saw arbor	Adjustable	Adjustable	Adjustable
Link chain lubrication system (mechanical type)	Standard	Standard	Standard
No. of pressure rollers	6	8	8
Distance from saw blade to machine frame (mm)	460	460	660
Table width at left of saw blade(L x W x H) (mm)	1500x850x800	1750x900x850	2100x1015x850
Table width at left of saw blade (mm)	405	455	425
Table width at right of saw blade(mm)	445	445	590
Net weight (kg)	950	1250	1750(HR-18) 2000(HP-20)
Packing weight (kg)	1050	1350	1850 (HR-18) 2150(HR-20)
Packing dimensions (L x W x H) (mm)	1850x1560x1550	2160x1640x1580	2240x1800x1750 (HR-18) 2340x1800x1750(HR-20)

HEAVY DUTY MULTI – BLADE RIP SAW

MODEL	HM14-6	HM14-2
Max. depth of cut	140mm	120mm
Max saw blade diameter	410mm(16")	360mm(14")
Useful length of saw blade bush	300mm	300mm
Width of feed chain	300mm	300mm
Power of saw motor	50HP (60HP,75 HP)	50HP (60HP,75 HP)
Feed motor	3 HP	3 HP
Speed of saw arbor	3200rpm	3200rpm
Variable feed speed of chain	6.7~35 M/min	6.7~35 M/min
Net weight	2000kg	1830kg
Packing weight	2200kg	1980kg
Packing dimension (L x W x H)	1850x1700x1700mm	1850x1550x1600mm

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!