



STRAIGHT LINE RIP SAW & MULTI – BLADE RIP SAW

**Superior quality
Maximum dependability of performance**

- Exclusively designed lubricator provides excellent lubrication performance
- Convenient link chain tracking adjustment
- Accurate link chain feed ensures superior straight accuracy
- Ruggedly constructed throughout for maximum stability of operation
- Precision saw arbor gives accurate and smooth cut
- Special request for all safety guard and bottom anti- kickback fingers



HR-20 / HR-18

Gluing length range : 300-3200mm

Max. Depth of cut : 135mm (HR-20), 120mm (HR-18)

Max. Sawblade diameter : 510mm (HR-240), 460mm (HR-18)

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

PT. Valtekindo Global Intertek

SAWBLADE LOCATED ABOVE LINK CHAIN

As shown in this configuration, the cutting force against the wood acts downward, minimizing possibility of chips kickback



EXCLUSIVE LUBRICATOR (PATENTED)

The lubricator delivers oil to link chains, specially designed lubricator allows lubricant flow synchronizing with chain feed speed lubrication effect



ACCURATE FENCE

The cast iron fence moves on the tubular rail with positive lock. A graduated scale is provided on the rail for accurate reading of fence positioning



POWERED ELEVATION OF PRESSURE MECHANISM (OPTIONAL)

The pressure mechanism is raised or lowered by power drive for maximum convenience of position adjustment



LASER UNIT (OPTIMAL)

When requested, the laser unit can be fitted on this machine for accurately guiding the saw path

HO-14