



F15 THIN CUTTING FRAME SAW

HIGH PRECISION HIGH EFFICIENCY

- Single, two ,or multiple wood cutting as desired
- Reduces material loss to a minimum
- Extremely fine surface effect



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



MICRO-COMPUTER CONTROL

- The machine is equipped with a PLC control for maximum operation convenience
- Electronic components and circuit design fully meet CE safely regulations
- Comprehensive anti-interference protection devices
- Self- diagnostic functions and warning lamp displays



GUIDE FENCE AT SIDE

In case the guide fence is mounted at the side, the machine allows for cutting a single wood material



GUIDE FENCE AT CENTER POSITION

In case the guide fence is mounted at the center position the machine allows for cutting two wood materials at a time for increasing efficiency



MULTIPLE GUIDE FENCE

Upon request the machine is available to be supplied with several guide fence, fence sizes can be specified by the customer. The use of multiple guide fences enables the machine to cut several wood materials at a time



CHOICE OF VARIOUS SAWBLADES

- Upon request, the machine can be supplied with A choice of various steel welded saw blade or T.C.T saw blades
- The customer may choose various saw blade thicknesses from 1.1 to 1.4 mm to suit various wood materials

CENTRALIZED PRESSURE REGULATIONS

- Each pressure roller is equipped with an independent pressure regulator for individual air pressure adjustment
- All pressure regulation valves are centralized for convenient adjustment adjustments and maintenance.