



SUPER MD 4 Side Planer / Moulder



Vertical spindle adjustment up to 80 mm

It allows the fitting of different tools on the vertical spindle, eliminating troublesome cutter change. Multiple cutting operations can be performed from a single spindle configuration.



Centralized lubrication

The spindles are lubricated by the centralized lubrication system for convenience. Auto lubrication unit for table is standard.

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



Front and rear pressure plate

The front pressure plate features 'draw-back' performance, which fully prevent damage to the cutters caused by too high work pieces. The rear pressure plate provides extremely uniform holding pressure for outstanding parallelism accuracy of machining.



Centralized control panel

All machine controls are centralized on the control panel for operation convenience. Symbols on the control panel provide easy understanding of each control switch. Feeding speed by inverter control and easy to see digital readout gauge are optional.



Vertical spindle with jointer device (optional) ~ for high speed

Vertical spindle with remote-controlled straight knife jointer and automatic profile jointers provide high speed feeding while maintaining superior surface quality. The design ensures a long service life, accuracy and precision.



Pneumatic cylinder for chip breaker on top spindle

The attachment is standard for MD-300 mm and high feeding speed series-60M/80M/ per min. for other models it is optional. Mechanical digital readout on the front and rear of top spindle is standard.