



SPECIFICATIONS:

MODEL	HK-1020W	HK-635ARD
Maximum width of plane	1020mm (40")	635mm (25")
Maximum height of plane	200mm (8")	200mm (8")
Minimum thickness of plane	10mm	10mm
Minimum length of plane	310mm	310mm
Number of knives	350pcs	180pcs
TCT knife size	TCT15x15x2.5mm	TCT30x12x1.5mm
Cutterhead diameter	φ 131mm	φ 126mm
Cutterhead speed	4000rpm	5000rpm
RPM of stepless variable speed	7-20m/min	7-40m/min
Dust hood outlet	6" x 4	6" x 2
Table surface	1016 x 2616mm (40"x103")	686 x 2616mm (27"x103")
Top cutterhead drive motor	40HP (50HP)	25HP
Bottom cutterhead drive motor	30HP (40HP)	20HP
Feed drive motor	7.5HP	5HP
Table elevation motor	1HP	1/2HP
Machine dimensions (LxWxH)	2750x1950x1900mm	2667x1145x1720mm
Net weight	6300kg	3000kg
Packing dimensions (LxWxH)	2850x2050x2050mm	2767x1245x1870mm
Gross weight	7000kg	3500kg

• All specifications, dimensions and design characteristics shown in this catalog are subject to change without notice.



Wider 8 Spiral Cutterhead (Standard)

The supporting base for 8 spiral cutterhead is standard. It ensures quieter operations even when working wider workpieces.



Outfeed Support Roller Table

The model is equipped with infeed and outfeed support roller tables for infeeding and outfeeding wider stock.



Side Adjustable Work Bench

The side adjustable handwheel for easy setting-up of jointing table height. With worm gear system and mechanical digital readouts for micro-adjustment.



Main Motor Pneumatic Brake

The emergency stop main motor pneumatic brake meets CE regulations.

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!