



AUTO RAISED PANEL DOOR MACHINE




Stackable Spindle

Locates to different cutter location at the touch of a switch, eliminating all set-up time. Brazed or insert tooling is available



• Door Templates

Includes 4 panel arches and 4 matching rails for different door size by simply lowering the roller to the required template level, and then an arched panel or rail can be produced



All 5 components of a raise panel door can be produced in less than 5 minutes by operator !

Model	LH-1000-AT	LH-1400-AT	LH-2200-AT
Main spindle driving power	7.1/2 HP	10HP	18 HP
Pump motor	1 HP	1 HP	1 HP
Main spindle revolving speed	9000r.p.m	9000r.p.m	9000r.p.m
Main spindle dia.	Ø1-1/4" (30m/m)	Ø1-1/4" (30m/m)	Ø1-1/4" (30m/m)
Driven wheel dia.	Ø100m/m	Ø100m/m	Ø100m/m
Max. working length	1000m/m	1400m/m	2200m/m
Machine size	1950x950x1450m/m	2350x950x1450m/m	3500x950x1450m/m
Packing size	2030x1000x1600m/m	2450x1000x1600m/m	3930x1200x1700m/m
N.W./G.W.	950/1150kgs	1020/1220kgs	1520/1720kgs

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!