



Model	LH-80-3P	LH-80-4PS	LH-100-3PS	LH-100-4PS	LH-60	LH-80	LH-100	LH-120	LH-60-D	LH-80-D	LH-100-D
Cutting capacity	12"~80"		24"~100"		6"~60"	12"~80"	24"~100"	28"~120"	6"~60"	12"~80"	24"~100"
Max. cutting length to width ratio	71.4"X35.7"		89.2"X44.6"		55.2"X27.6"	71.4"X35.7"	89.2X44.6"	10"55"	55.2"X27.6"	71.4X35.7"	89.2X44.6"
Table diameter	Ø62"		Ø72"		Ø46"	Ø62"	Ø72"	Ø83"	Ø46"	Ø62"	Ø72"
Table speed	0.5-3r.p.m		0.5-3r.p.m		0.5-3r.p.m	0.5-3r.p.m	0.5.3 rpm	0.5.3 rpm	0.5.3 rpm	0.5.3 rpm	0.5.3 rpm
Spindle speed	9000 rpm		9000 rpm		9000 rpm	9000 rpm	9000r.p.m	9000r.p.m	9000r.p.m	9000r.p.m	9000r.p.m
Spindle diameter	Ø30mm		Ø30mm		Ø30mm	Ø30mm	Ø30mm	Ø30mm	Ø30mm	Ø30mm	Ø30mm
Spindle height	5.5"		5.5"		5.5"	5.5"	5.5"	5.5"	5.5"	5.5"	5.5"
Max. cutter diameter range	Ø200mm		Ø200mm		Ø200mm	Ø200mm	Ø200mm	Ø200mm	Ø200mm	Ø200mm	Ø200mm
Follower wheel diameter	Ø100mm		Ø100mm		Ø100mm	Ø100mm	Ø100mm	Ø100mm	Ø100mm	Ø100mm	Ø100mm
Table drive motor	2 HP/DC		3 HP/DC		2 HP/DC	2 HP/DC	3HP/DC	3HP/DC	2HP/DC	2HP/DC	3HP/DC
Cutter head drive motor	10 HPx2		10 HPx2		10 HPx2	10 HPx2	10 HPx2	15 HPx2	10 HPx2	10 HPx2	10 HPx2
Sanding attachment motor	1 HPx1	1 HPx1, 3HPx1	1 HPx1	1 HPx1, 3 HPx1	-	-	-	-	-	-	-
Net weight (kg)	3500kgs	3600kgs	3900kgs	4000kgs	2200kgs	3400kgs	3800kgs	4600kgs	2400kgs	3500kgs	4000kgs
Gross weight (kg)	4000kgs	4100kgs	4600kgs	4700kgs	2700kgs	3700kgs	4300kgs	5200kgs	2700kgs	3800kgs	4500kgs
Machine size (mm)	3500x2175x1778		4490x2692x1878		2159x1905x1778	2600x2175x2220	3200x2692x1878	3800x3200x1878	2220x1980x1950	2580x2430x1950	3270x2760x1878
Packing dimensions (mm)	3700x2250x2220		4670x2260x2220		2260x1910x2220	2800x2250x2220	3272x2260x2220	3980x2260x2220	2400x2180x2220	3000x2290x2220	3372x2260x2240

Note :

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!