



SPINDLE MOULDERS

FEATURES

- **INTERCHANGABLE SPINDLES:**
- Choose from five spindle diameters: 1", 1-1/4", 30mm, 35mm and 40mm. Also available is a 50mm diameter fix spindle.
- **QUICK CHANGE SPINDLE SPEEDS:**
- 4 spindle speeds can be achieved when driven by a pulley. By simply loosening a lock lever and shifting the assembly, the speed may be changed quickly and efficiently.
- **REVERSIBLE SPINDLE ROTATION.**
- **TABLE INSERTS:**
- A wide variety of cutter shapers can be used as the spindle is fitted with three insert rings. The maximum insert opening diameter is 350mm.
- **FENCE:**
- All micro-adjustable fence guarantee fence accuracy with micro adjustment knob and precise size. A 2-piece outlet dust hood is attached to the fence assembly and the machine base under the table.
- **TABLE:**
- The large, extra-heavy, iron-cast table is surface precision ground and is also rib-reinforced for maximum rigidity.
- **ROUTING:**
- The machine spindle can accept router bits.
- Guaranteed full power 5HP drive motor (HS-100 series).
- Guaranteed full power 7.5HP drive motor (HS-120 series).
- Complete dust hood device.
- Gravity indicator for tilting head wheel.
- Front hand wheel operation
- Extra fix tilting spindle device.



Complete dust hood system



CE type safety guard & pressure unit for Fence (optional)



HS-100TS / HS-120TS



Extra fix tilting spindle device.



Gravity indicator for tilting hand wheel.



HS-100T / HS-120T



HS-100 / HS-120



HS-100S / HS-120S



(With extension table & front support) HS-100L / HS-120L

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!