



625 serie Spindle Shapers



HS-625M

- Fixed table
- Table area: 41-3/8" x 31-1/2" (1050 x 800mm)



HS-625T

- Tilting spindle
- Table area: 41-3/8" x 31-1/2" (1050 x 800mm)



HS-625MS

- Hand feed sliding table
- Table area: 41-3/8" x 31-1/2" (1050 x 800mm)



HS-625TS

- Tilting spindle
- Hand feed sliding table
- Table area: 41-3/8" x 31-1/2" (1050 x 800mm)

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



QUICK-CHANGE SPINDLE SPEEDS:

The V-belt can be quickly released when changing speeds by simply loosening one lock lever and shifting the entire assembly.



TILTING SPINDLE: (Models 625T and 625TS)

Accurate angle cutting from -5° ~ 90° ~ +45° can be achieved by tilting the spindle using the handwheel conveniently placed at the front. Precise angle setting can be done with the tilt scale.



SPINDLE BRAKE:

The spindle can be stopped quickly by using the foot brake which immediately cuts the electricity, thereby upgrading work efficiency and safety.



SLIDING TABLE: (Models 625MS and 625TS)

The sliding table is precision constructed for maximum slide accuracy, providing effortless movement for hand-feed operations. When not in use, the sliding table may be locked. There is a one-piece toggle clamp with

slide fence and adjustable clamping thickness with length stop.