



Tilting Arbor Saw

Overarm saw Suva guard (Optional)



EXCLUSIVE RIP FENCE AND GUIDE RAIL ASSEMBLY

New type fence assembly slides on the front and rear guide rail smoothly by means of a plastic pad.

Single clamp handle locks fence to front guide rail. Parallelism to the saw blade is conveniently adjustable by screw

Guide rail is calibrated in inches and millimeters and has a magnifier for good visibility

Specification

MODEL	TBS-400	TBS-350	TBS-300	TBS-250
Saw blade diameter	16" (405mm)	14" (350mm)	12" (305mm)	10" (250mm)
Max. depth of cut at 90°	6" (152mm)	5" (125mm)	4" (101.6mm)	3" (76mm)
Max. depth of cut at 45°	4 1/4" (108mm)	3 1/2" (88mm)	2 3/4" (70mm)	2" (54mm)
Arbor diameter	1" or 30mm	1" or 30mm	1" or 30mm	1" or 30mm
Arbor speed	3750 RPM	3750 RPM	3850 RPM	4200 RPM
Main table size	48" x 38" (1220 x 965mm)	48" x 38" (1220 x 965mm)	48" x 30" (1220 x 762mm)	36" x 27" (915 x 685mm)
Table height	34 1/4" (857mm)	34 1/4" (857mm)	34 1/4" (857mm)	34 1/4" (857mm)
Sliding table size	30" x 26" (760 x 660mm)	30" x 26" (760 x 660mm)	30" x 26" (760 x 660mm)	30" x 18" (760 x 460mm)
Sliding table stroke	60" (1525mm)	60" (1525mm)	60" (1525mm)	44" (1118mm)
Sliding table capacity	4" x 8" (1220 x 2440mm)	4" x 8" (1220 x 2440mm)	4" x 8" (1220 x 2440mm)	3" x 6" (914 x 1828mm)
Max. rip to right of blade	49" (1245mm)	49" (1245mm)	38" (965mm)	25" (635mm)
Motor	7.5 HP standard 10 HP	5 HP standard 7.5 HP optional	3 HP standard 5 HP optional	2 HP standard 3 HP, 5 HP optional
New weight	869 lbs (395 kgs)	847 lbs (385 kgs)	572 lbs (260 kgs)	407 lbs (185 kgs)
Gross weight	1034 lbs (470 kgs)	1012 lbs (460 kgs)	704 lbs (320 kgs)	495 lbs (225 kgs)
Packing size (L x W x H)	37" x 44" x 42"	37" x 44" x 42"	32 x 36" x 42"	29" x 36" x 42"

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!