

CONVENTIONAL LATHE



DY 460X1100G



CONVENTIONAL LATHE
DY-410G~510G
BED WIDTH 330MM
DY 460X1100G

Note :
 Due to keeping innovation,
 the specification and
 Machine pictures or color
 are subject to alteration
 without notice!

	MODEL	DY-410G	DY-450G	DY-510G
Boring	Maximum boring diameter	1300 (1800) (2200) (3000) mm		
	Boring over bed	410mm	450mm	510mm
	Boring over tool slide	330mm	330mm	330mm
	Boring over Q.D.T	330mm	330mm	330mm
	Height of toolholder (over bed)	330mm	330mm	330mm
Bed	Bed width	330 mm		
Headstock	Spindle nose	D1-E	D1-F, 20mm	
	Spindle speed (RPM)	12 change	D1-F: 30-2000 rpm / D1-E: 30-1000rpm	
	Number of spindle speed	12 change		
Feeds-Thread	Feedstock	800 rev. 2 P.I. in 4 pass		
	Number of feed changes	80		
	Longitudinal feed range	0.05-1.2 mm/rev		
	Cross feed range	with hand wheel 0.05-0.3 mm/rev, without hand wheel 0.3-1.0 mm/rev		
	Multi-Thread	41 ends 2-121 P.I.		
Tool slide	Tool holder	350 mm		
	Compound rest height	120 mm		
	Tailstock	Quill travel	50 mm	
Motor	Main motor	Metric		
	Coolant pump	3 phase / 3-wire / 380V		
Packing size	Overall size (mm)	1100mm	1500mm	1700mm
	H x W x D	2200 x 1100 x 1700	2200 x 1100 x 1700	2200 x 1100 x 1700
	Weight (kg)	2200	2200	2200
Weight (approx.)	H x W x D (mm)	2200 x 1100 x 1700	2200 x 1100 x 1700	2200 x 1100 x 1700
	Weight (kg)	2200	2200	2200

MADE IN CHINA (FOR EXPORT) AND QUALITY CONTROLLED FOR EXPORT (FOR EXPORT)

www.vgimachine.com