

STANDARD ACCESORIES

3-JAW CHUCK / $\Phi 325$ & FLANGE, DEAD CENTERS, REDUCTION SLEEVE, MAINTENANCE KIT, FOUNDATION BOLTS / NUTS, LEVEL BLOCKS, MACHINE TOOL MANUAL, [CENTERS DISTANCE IS MORE THAN 2000MM / (INCLUDE 2000MM) FOR $\Phi 200$ STEADY REST $\Phi 20-140$ FOLLOW REST]

OPTIONAL ACCESORIES

4-JAW CHUCK & FLANGE, FACE PLATE, DRIVE PLATE, STEADY REST (LESS THAN 2000MM), FOLLOW REST (LESS THAN 2000MM), $\Phi 130$ SPINDLE BORE, ELECTRIC TURRET, ELECTRIC QUILL, TAPER TURNING ATTACHMENT.

(IN LINE WITH THE POLICY OF CONTINUED DEVELOPMENT THE MANUFACTURER RESERVES THE RIGHT TO AMEND THE SPECIFICATIONS WITHOUT PRIOR NOTIFICATION, THE PICTURES AND DATE IN THE STYLEBOOK ARE CONSULT ONLY, IF THERE IS FLUCTUATION, ACCORDING TO THE REAL OBJECT PLEASE.)



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

CW 6 1/2 63C
CW 6 1/2 73C
CW 6 1/2 83C
CW 6 1/2 93C

SPECIFICATION:

Model		Unit	CW6163C CW6263C	CW6173C CW6273C	CW6183C CW6283C	CW6193C CW6293C
Swing over bed		mm	630	730	830	930
Swing in gap		mm	800	900	1000	1100
Swing over cross slide		mm	350	450	550	650
Distance between centers		mm	750, 1000, 1500, 2000, 3000, 4500, 6000			
Length in gap from face plate		mm	300			
Spindle nose			C11 or B11			
Spindle bore		mm	105, 130			
Spindle speeds		rpm / steps	10-800 / 18			
Cross slide travel		mm	480			
Top rest travel		mm	225			
Rapid traverse		mm / min	纵向Axe Z: 3200, 横向Axe X: 1900			
Quill diameter		mm	90			
Quill travel		mm	260			
Quill taper			MT5			
Bed width		mm	550			
Metric threads		mm / kinds	1-240 / 53			
Inch threads		tpi / kinds	30-2 / 31			
Module threads		mm / kinds	0.25-60 / 46			
Diametral pitch threads		lpi / kinds	60-0.5 / 47			
Main motor power		kw	11			
Packing size	Length	mm	3460, 3390, 3795, 4330, 5310, 6810, 8310			
	Width	mm	1400			
	Height	mm	2000			
Gross weight	Kg		4250	4450	4650	4900
			4500	4700	5100	5300
			5000	5200	5600	5800
			5500	5700	6100	6300
			6200	6400	6600	6900
			7300	7500	7600	7900
			8300	8500	8600	8700