



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

Specifications	Units	GMC1225A	GMC1225 (x 向线规)
Worktable longitudinal travel	mm	2000	2700
Slide carriage transverse travel	mm	1700	1700
Milling head vertical travel	mm	750	1000
Worktable size	mm	2500 × 1250	2500 × 1250
Max. load of worktable	kg	6000	5000
Number/Width/Distance of T-slot	mm	7-28-160	7-28-160
Gantry width	mm	1600	1750
Distance from spindle end to worktable surface	mm	150-900	150-1150
Spindle taper		BT50	BT50
Spindle speed	rpm	30-4000	30-3200
Spindle motor power	kW	15/18.5	15/18.5
X,Y axis	mm/min	1-4000	1-4000
Z axis	mm/min	1-2000	1-2000
X,Y axis	mm/min	10000	12000
Z axis	mm/min	8000	8000
X,Y,Z axis	mm	0.030、0.025、0.022	0.030、0.025、0.022
X,Y,Z axis	mm	0.014、0.013、0.012	0.014、0.013、0.012
Overall dimension	mm	7200 × 4000 × 4500	7200 × 4000 × 4500
Machine weight	kg	24000	23000