

Bench CNC Milling Center

stepper Only



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!



Blow of ring



ISO 20 / ER16 spindle taper

A 6mm ER16 collet as standard accessory



4 station ATC
Variety of tools for your choice



Pneumatic door



Pneumatic device



Specification

TABLE	Table size	400×145mm
	T slot (amount×width×distance)	3×12mm×40mm
	Max. load	20Kg
TRAVEL	X travel	260mm
	Y travel	152mm
	Z travel	180mm
	Spindle nose to table	60-240mm
	Spindle center to column	200mm
SPINDLE	Spindle taper	ISO20
	Spindle motor	1000W
	Spindle speed	5000r/min
FEED stepper	The max moving speed	2000mm/min
	The max feeding speed	500mm/min
	Power of motor X/Y axis	1.35Nm
	Power of motor Z axis	2.2Nm
TOOL CHANGER	Tool number	4
	Max.tool diameter	10mm
	Max.tool length	110mm
	Max.tool weight	0.5Kg
	Time of tool changing	10s
ACCURACY	Positioning accuracy	0.015mm
	Repeatability accuracy	0.01mm
	Pneumatic supply	0.6 MPa
OTHERS	Power	230V or 120V
	Weight (NW/GW)	280/340Kg
	Overall dimension	1040×860×940mm
	Packing size	1170×960×1100mm

Transparence enclosure is selectable.
(more suitable for education)



Clamping Kit



42 pcs.
S/N10047

High Precision Machine
Vise



Width 100mm
S/N10602

4 tool ISO 20/ER16
tool holder



S/N10520

ER16 Collet set - 8 pieces



(3,4,5,6,7,8,9 and 10mm)
S/N10608