

自动嵌线机 COIL INSERTING MACHINE



QX01无分度液压嵌线机
Coil inserting machine (hydraulic/no indexing)



QX02 / QX02L无分度伺服嵌线机
Coil inserting machine (servo/no indexing)



QX21有分度液压嵌线机
Coil inserting machine (hydraulic/with indexing)



QX22有分度伺服嵌线机
Coil inserting machine (servo/with indexing)

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

名称及型号	QX01无分度液压嵌线机	QX02 / QX02L无分度伺服嵌线机	QX21 / QX22分度液压/伺服嵌线机
Description	Coil inserting machine (hydraulic/no indexing)	Coil inserting machine (hydraulic/no indexing)	Coil inserting machine (servo/with indexing)
定子叠厚Stator stack height ☆	5mm ~ 130mm	5mm ~ 130mm / 5mm ~ 230mm	5mm ~ 130mm
定子外径Stator O.D. ☆	≤ Φ160mm	≤ Φ160mm	≤ Φ160mm
定子内径Stator I.D. range ☆	Φ17mm ~ Φ100mm	Φ17mm ~ Φ100mm	Φ17mm ~ Φ100mm
分度方式	/	/	油压马达/步进电机
生产节拍Tact time	0.4 ~ 1.5S/槽 (打纸时间) s/slot	0.4 ~ 1.5S/槽 (打纸时间) s/slot	0.4 ~ 1.5S/槽 (打纸时间) s/slot
气源Air pressure	/	0.5 ~ 0.8MPa	- / 0.5~0.8Mpa
电源Power supply	380V/50~60HZ三相四线 Three-phase four-wire	380V/50~60HZ三相四线 Three-phase four-wire	380V/50~60HZ三相四线 Three-phase four-wire
功率Power	3.75KW	2.5KW	3.75KW / 2.5KW
外型尺寸(长宽高)	1500mm×800mm×1450mm	1500mm×740mm×1600mm	1500mm×800mm×1450mm
Dimension (L×W×H)		2200mm×800mm×1450mm	
重量Weight	≈1000Kg	≈1000Kg / ≈1050Kg	≈1100Kg / ≈1000Kg

☆需通过更换模具
Through tooling replacement

※ 以上参数可根据客户要求重新设计及制造 All the referenced technical parameters can be designed and manufactured according to customer's request.

注：本公司保留改变产品技术规格和外观的权利，所载内容不作为订货验收的依据，如有变更，恕不另行通知。

Note: We reserve the right to change the technical specifications and the appearance of products. The contents contained are not as a basis for acceptance. Specifications are subjected to change without further notice.