



金康精工

绑线机

COIL LACING MACHINE



Note:

Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



BX08全伺服双头单工位自动绑线机
Double side lacing machine(full-servo/one station)

名称及型号	BX08 / BX11A-IV全伺服双头单工位自动绑线机	BX16双头副转工位伺服自动绑线机
Description	Double side lacing machine(full-servo/one station)	Double side lacing machine(full-servo/one station)
定子铁芯叠厚Stator stack height	15mm-180mm	15mm-180mm
定子铁芯外径Stator core OD. ☆	≤Φ190mm	≤Φ260mm
定子铁芯内径Stator core ID. ☆	≥Φ30mm	≥Φ100mm
绑线方式Lacing mode	每槽、隔槽或花式 Slot-by-slot/Slot-skipping/Fancy lacing	每槽、隔槽或花式 Slot-by-slot/Slot-skipping/Fancy lacing
绑线转速Lacing speed	0.2-0.4秒/针s/needle / 0.5-0.7秒/针s/needle	0.5-0.7秒/针s/needle
线包高度Coil height	≤55mm	≤55mm
气压Air pressure. ☆	0.4-0.7MPa	0.4-0.7MPa
电源Power supply	380V/50-60Hz三相四线Three-phase four-wire	380V/50-60Hz三相四线Three-phase four-wire
总功率Power	3.0Kw / 3.1Kw	5.85KW
外型尺寸(长宽高) Dimension(L×W×H)	1550mm×950mm×1800mm / 1550mm×1070mm×1800mm	2100mm×1100mm×1800mm
重量Weight	≈900kg / ≈950Kg	≈1000Kg

☆需通过更换模具

Through tooling replacement

※ 以上参数可根据客户要求重新设计制造。All the referenced technical parameters can be designed and manufactured according to customer's request.

注：本公司保留改善产品技术规格和外观的权利，所载内容不作为口头验收的依据，如有变更，恕不另行通知。

Note: We reserve the right to change the technical specifications and the appearance of products. The contents contained are not as a basis for acceptance. Specifications are subjected to change without further notice.