



串激电机设备SERIES EXCITED EQUIPMENT
转子设备ROTOR MACHINES

RX51C双飞叉转子绕线机
Rotor coil winding machine
(double-fly fork)



CZ50转子绝缘纸插入机
Rotor slot insulation machine



CZ52轮毂电机绝缘纸插入机
Slot insulation machine



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

名称及型号	CZ50转子绝缘纸插入机 / CZ52轮毂电机绝缘纸插入机	CP50转子槽契插入机
Description	Rotor slot insulation machine	Rotor slot wedge inserting machine
转子外径Rotor O.D. range ☆	Φ20-Φ80mm / Φ150-Φ250mm	Φ20-Φ80mm
转子叠厚Rotor stack height ☆	15-65mm可调(更长可特殊制作)	15-65mm可调(更长可特殊制作)
	15-65mm adjustable(Special making for longer)	15-65mm adjustable(Special making for longer)
转子槽数Rotor slot no. ☆	8-36 / 8-70	8-36
绝缘纸宽度 (Max)Max-slot insulation paper width ☆	30mm / 40mm	8mm
电源Power supply	220V±10% AC (50/60Hz)	220V±10% AC (50/60Hz)
工作气压Air pressure	0.4-0.7Mpa	0.4-0.7Mpa
外型尺寸 (长宽高) Dimension (L×W×H)	840x1500x1330mm / 840x900x1650mm	840x1500x1330mm
重量Weight	250Kg	250Kg

名称及型号	RX51A双飞叉转子绕线机	RX51B双飞叉转子绕线机	RX51C双飞叉转子嵌线机
Description	Rotor coil winding machine (double-fly fork)	Rotor coil winding machine (double-fly fork)	Rotor coil winding machine (double-fly fork)
转子外径Rotor O.D. range ☆	Φ20-Φ60mm	Φ20-Φ60mm	Φ20-Φ60mm
转子叠厚Rotor stack height ☆	20-60mm(更长可特殊制作) (Special making for longer)	20-60mm(更长可特殊制作) (Special making for longer)	20-60mm(更长可特殊制作) (Special making for longer)
转子槽数Rotor slot no. ☆	8-36槽(偶数) (even)	8-36槽(偶数) (even)	8-36槽(偶数) (even)
转子轴径Rotor shaft diameter ☆	Φ3-Φ12mm	Φ3-Φ12mm	Φ3-Φ19mm
换向器外径Commutator O.D. range ☆	Φ15-Φ40mm	Φ15-Φ40mm	Φ15-Φ40mm
转子轴长Rotor shaft length ☆	80-220mm	80-220mm	80-220mm
线径范围Wire diameter range ☆	Φ0.1-Φ1.0mm	Φ0.1-Φ1.0mm	Φ0.6-Φ1.2mm
最高转速/额定转速	3000 (空载) /2000r/min	3000 (空载) /2000r/min	3000 (空载) /2000r/min
Max/rated rotate speed	3000 (no load) /2000r/min	3000 (no load) /2000r/min	3000 (no load) /2000r/min
电源Power supply	三相380V AC 50/60Hz	三相380V AC 50/60Hz	三相380V AC 50/60Hz
	3-phase 380V AC 50/60Hz	3-phase 380V AC 50/60Hz	3-phase 380V AC 50/60Hz
工作气压Air pressure	0.5-0.7Mpa	0.5-0.7Mpa	0.5-0.7Mpa
工作方式Working mode	单机Single machine	连接皮带线Connecting to conveyor line	带锯齿线With jaggies

☆需通过更换模具
Through tooling replacement

※ 以上参数可根据客户要求重新设计及制造 All the referenced technical parameters can be designed and manufactured according to customer's request.

注：本公司保留改变产品技术规格和外观的权利，所载内容不作为订货验收的依据，如有变更，恕不另行通知。
Note: We reserve the right to change the technical specifications and the appearance of products. The contents contained are not as a basis for acceptance. Specifications are subjected to change without further notice.