



X-5036A KNEE TYPE MILLING MACHINE



X5036A 是一款立式铣床，功率大，加工范围广，二轴自动进给，Z轴电动升降，硬化处理。

X5036A is a vertical milling machine, high-power, processing range widely, automatic feed on two axes, motorized lift on Z axis, hardened

Note :
Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

主要技术参数	Specifications	X5036A
主轴锥孔	Spindle taper	ISO50
主轴中心到工作台距离	Distance from spindle nose to table (mm)	60-460
主轴中心到立柱导轨距离	Distance from spindle axis to column guideway (mm)	325
主轴转速范围	Spindle speed range (r.p.m)	12 rank60-1700
立铣头回转角度	Swivel angle of vertical milling head	±45°
工作台尺寸	Table size (mm)	1250×360
工作台行程	Table travel (mm)	600/300/400
工作台纵、横向机动进给范围	Range of longitudinal cross travel (mm/min)	(8rank) 30-740rapid1080
工作台垂向机动升降速度	Zspeed of table (mm/min)	590
工作台“T”型槽 (槽数/宽度、间距)	T-slot of table(number-width-length)	3/18/80
主传电动机功率	Main motor (KW)	4
工作台机动电机功率	Motor for rapid device of table(X,Y) (KW)	0.75
升降台机动升降电机功率	Motor for vertical device of table(Z) (KW)	0.75
冷却泵电机功率	Cooling pump motor power (KW)	0.09
冷却泵流量	Cooling pump flow	25 L/M
外形尺寸	Overall dimensions (mm)	1700×1680×1880
净重/毛重	N. W/ G. W (kg)	2200/2300