



- For electronic parts, mould and hole, slot and frame processing
- Twice precisely scraping could assure the quality of processing.
- Fit for boring, milling, drilling and boring tolerance is 0.005–0.012mm
- Taiwan original milling head, NSK P4 spindle bearing
- Spindle tolerance: 0.002mm
- Parallel value between table's movement and table: X axis 0.015mm, middle 0.01mm, Y axis, 0.01mm
- Variable speed and inverter speed milling head is available

STANDARD ACCESSORIES

- * Way Cover
- * Working Light
- * Tool & Toolbox

OPTIONAL ACCESSORIES

- * Clamping Kit
- * Elevating Motor
- * Milling Chuck
- * Coolant Pump
- * 6" Vise
- * Power BER
- * Power Feed/Mechanical Feed

PRECISE TURRET MILLING MACHINE



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

M5-Inverter



M6B-Variable



M7-Variable



Model		M2	M3	M4	M4A/M5	M5A/M5B	M6A/M6B	M7	M8
Table Size(mm)		1067x230x72 1244x230x72	1270x254x90	1270x254x90	1270x245x90 1370x254x90	1270x254x90 1470x305x90	1370x330x99	1370x330x99	1524x360x99
Travel	Longitudinal(mm)	▲ 750 ▲ 900	900	900	▲ 900 ▲ 1000	▲ 800 ▲ 1000	▲ 850 ▲ 1000	▲ 1000	▲ 1150
	Cross (mm)	▲ 325	395	405	■ 370 ■ 430	■ 415	■ 395	■ 500	■ 500
	Vertical(mm)	▲ 360	350	340	■ 360 ■ 390	■ 430	■ 350	■ 500	■ 500
Travel of Spindle Quill(mm)		127	127	127	127	150	150	150	140
Max.Distance from the Spindle Nose to Table(mm)		440	400	450	400 440	560 590	570	680	690
Spindle	Rotation Speed(rpm)	Step speed: 80–5440(16 gauges) Variable speed: 60–4200 Inverter speed: 0–4200				Step speed: 80–5440(16 gauges) Variable speed: 70–3600 Inverter speed: 0–4200			
	Taper	R8(NT30)	R8(NT30)	R8(NT30)	R8(NT30)/Nt40	NT40	NT40	NT40	NT40
	Rated Power(HP)	3	3	3	3	5	5	5(7.5 optional)	7.5
Tilt Angle	Forward and Backward	± 45°	± 45°	± 45°	± 45°	(± 45° optional)	± 45°	± 45°	0°
	Left and Right	± 90°	± 90°	± 90°	± 90°	± 90°	± 90°	± 90°	± 90°
Dimension(LxWxH)(mm)		1400x1500x2100 1400x1700x2100	1500x1700x2150	1500x1700x2200	1500x1700x2150 1600x1800x2150	1500x1700x2450 1500x1900x2450	1600x2000x2450	2000x2000x2750	2300x2000x2900
Net Weight(kg)		1000	1280	1400	1500	2000 2100	2200 2300	2700	2900