

HD-780CE Needle Detector

Characteristics:

1. Adopting imported high-end e-shielding technology, to exclude all outer interference;
2. The amount of qualified products, unqualified products and the total amount of products can be calculated;
3. Applicable for thick or super-thin objects separately;
4. Has the alarm system when the belt leaves the normal track, to ensure the life length of the belt as long as it can be;
5. Equipped with auto-starting device;
6. With the design of environment protection concept, auto electricity saving;
7. With environment monitor and location indicator for broken needles;
8. Auto alarming and auto-return function;
9. Anti-interference and anti-seismic function, high stability and high sensitivity.



Technical parameters:

Detecting Mode	: Magnetic Induction
Detecting Ability	: CII 1.20mm Ferrous Fragment
Detecting Adjustment	: Step-less Adjustment
Detecting width	: 600mm
Detecting height	: 160mm (Standard Type)
Alarm mode	: Beep
Belt Speed	: (Approx) 30m/min
Power Supply	: Single-phase 220V, 50Hz
Rated Output	: (Approx) 110W
Dimension	: 1650(L) x 1050(W) x 900(H)mm
Weight	: (Approx) 250kg



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

