

HD-1200CE Needle Detector

Characteristics:

1. Because of wide detecting channel, this machine is used for detecting the bedding and other wide articles.
2. This machine features human-machine interface, can respectively calculate the qualified products, rejects and total amount;
3. It can detect the thick materials and super thin materials;
4. This machine is equipped with automatic adjusting apparatus which can correct the conveyor.
5. This machine has the self-protection function which can start the machine only after removing the fault under the protection status.
6. Fully-computer designing, automatic control switch which can prevent pushing the start button frequently in order to prolong the life of switch
7. With environment interference indicator and broken-needle indicator;
8. Automatic alarm of broken needle, and automatic return, the distance of return can be set at will;
9. This machine features the good immunity, good reliability, and high sensitivity.

Parameter:

Detecting Mode	: Magnetic Induction
Detecting Capacity	: Iron ball ϕ 1.20mm
Sensitivity set	: Stepless
Detecting width	: 1200mm
Detecting height	: 150mm
Alarm mode	: Beep
Conveyor speed	: about 30m/min
Power	: Single-phase 220V, 50Hz
Consumed power	: about 165W
Dimension	: 1650(L) x 1650(W) x 960(H)mm
Weight	: about 360kg



Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!

