



HD-760CE-20 NEEDLE DETECTOR SPECIAL FOR TOYS

PRODUCT FEATURES:

Designed specially for toys, based on the characters of toys, with the feature of magnetic interference resistance, shake resistance, electromagnetic radiation resistance, run stably, and easy maintenance.

1. Wide detecting channel, widely used for toys, towels, beddings and other thick objects;
2. The amount of qualified products, unqualified products and the total amount of products can be calculated respectively;
3. Automatically adjust the belt deviation device, the belt will not be deflected;
4. With alarm system, when the belt leaves the normal track, to ensure the life of the belt as long as it can be;
5. Equipped with computerized start-and-stop device;
6. With the design of environment protection concept, auto electricity saving;
7. With environment monitor and location indicator for broken needles and ferrous fragment;
8. Auto-alarm when broken needle or ferrous fragment is detected. Auto-return function, the return distance can be adjusted for big or small objects at will;
9. Anti-interference and high stability, high reliability and high sensitivity.

Technical Parameter

Detecting Mode	: Magnetic Induction
Detecting Ability	: ϕ 1.20mm ~ 2.00mm Ferrous Fragment
Detecting Adjustment	: Step-less Adjustment
Detecting width	: 600mm
Detecting height	: 200mm (Standard type) ~ 300mm
Alarm mode	: Beep
Belt Speed	: (approx) 30m/min
Power supply	: Single-phase 220V, 50Hz
Rated Output	: (approx) 110w
Dimension	: 1650 (L) x 1050(W) x 900(H)mm
Weight	: (approx) 200kg



HD-980CE WIDE NEEDLE DETECTOR FOR FINISHED PRODUCTS

PRODUCT FEATURES:

This model is mainly used for the finished products, to detect the scissors in the box, packing racks, blades, pens and other ferrous items left in the packing process.

1. Wide detecting channel 750mm(W) x 460mm (H), usually used for packed finish-products;
2. High-power transmission, conveying maximum load weight is 50 kg;
3. The amount of qualified products, unqualified products and the total amount of products can be calculated respectively;
4. Automatically adjust deviation of the belt, the belt will not be deflected;
5. With the alarm system, when the belt leaves the normal track, to ensure the life of the belt as long as it can be;
6. Equipped with computerized start-and-stop device;
7. With the design of environment protection concept, auto electricity saving;
8. With environment monitor and location indicator for broken needles and ferrous fragment;
9. Auto-alarm and auto-return function; The pusher for the unqualified products is optional;
10. Anti-interference and high stability, high reliability and high sensitivity.



Technical Parameter

Detecting Mode	: Magnetic Induction
Detecting Ability	: ϕ 5.00mm Ferrous Fragment
Detecting Adjustment	: Step-less Adjustment
Detecting width	: 750mm
Detecting height	: 460mm (Standard type)
Alarm mode	: Beep and Lamp
Belt Speed	: (approx) 30m/min
Power supply	: Single-phase 220V, 50Hz
Rated Output	: (approx) 200W
Dimension	: 1860 (L) x 1160(W) x 1260(H)mm
Weight	: (approx) 300kg



Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!

