



PERFORMANCE FEATURES

GH018-L type High stretch yarn is especially suitable for the chemical fiber yarn, thread, rope winding yarn into the bobbin state. The machine adopts computer control system, has single spindle control, automatic yarn refueling, shrinking side device, anti overlapping electronic device, yarn break automatic stop device, length setting device, overfeeding silk, slow start adjustable, the wire speed is adjustable and tension device such advanced technology as above, to ensure the high quality of this machine. It's characteristic: the wire speed is fast, once forming, the tension is even, the shape is beautiful. The machine is compact in structure and two sides in operation, with little floor space.

Note :
Due to keeping innovation,
the specification and
Machine pictures or color
are subject to alteration
without notice!



Technical characteristics	Technical Parameters
Grooved drum	Ordered separately
Take-up package	Ordered separately
Form of friction sticks, specifications(Ordered separately)	Flat tube $\phi 80 \times 220$ (big end); Inclined tube $\phi 80 \times 220$ (big end); 3.5° taper
Configuration	5spindles / section
Composition	Max. :12 section /set(60 spindles)
Max. package	$\leq 220\text{mm}$
Power supply	Three - phase five-wire system 220V/380V 50Hz, a spindle power 120W
Machine(5 spindles)weight and dimension	880kg 1454mm (length) $\times$ 1000mm(width) $\times$ 1700mm(height)