

GH018-230 Type High Speed Yarn Bobbin Winding Machine



INTRODUCTION

GH018-230

GH018-230type winder, used in chemical fiber, cotton yarn, yarn, low stretch yarn, winding into a cone or a cylinder, for the next process, it can make 3KG-4KG yarn of bobbin, good forming, without the phenomenon of edge collapse.GH018-230 type to alleviate the labor intensity of the process, adaptation high speed production. It is suitable for hank yarn to be changed into yarn or cylinder and after dyeing. (Can be customized 2 spindles, 4 spindles)

Technical characteristics	Technical parameters
Bobbin size	230mm
Structure	Single-sided machine, Each (5,10,15,20,25,30,35,40,45,50)spindles
Power Supply	Three phase 220V or 380V 50/60Hz
Drive	Single spindle independent AC motor drive
Power consumption	0.18kw/ spindle
The shaping bobbins	The circular column(5" / cone; 4" 20, 5" 57, 9" 15 cone
Drum diameter	A maximum of 200 and 290mm
Yarn speed	300-1000m/min
Anti overlapping electronic device	Inverter control
Length setting device	Programmable logic controller(PLC) control/ display the length
Tension device	Rotate self-cleaning tensioner and wax each spindle
Mechanical cleaning device	Fine-tuning machine cleaning knife for each spindle
Yarn break automatic stop device	Electronic break stop
Speed regulating device	Frequency control of motor speed
Soft package edge traverse device	Mechanical/ suitable for soft type winding machine
Electronic yarn cleaner	Optional
Air splicer	Optional
Blowing and suction cleaner	Optional
Lighting system	Lamp
Dimensions(mm)	2050*600*1500mm

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!