


VGI

GH018-B High Speed Yarn Cone To Cone Rewinding Machine



Customizable two spindles



GH018-B

- + Power saving
- + Time saving
- + Labor saving
- + Simple operation
- + High efficiency

Within Length calculator
= Create economic benefits, no
two years machine to help you
save the cost of purchase

DC single-spindle single control

PERFORMANCE FEATURES

GH018 B High speed yarn winder machine, used in chemical fiber, cotton yarn, yarn, low stretch yarn, winding into a cone or a cylinder, for the next process, good forming, without the phenomenon of edge collapse. GH018 B type to alleviate the labor intensity of the process, adaptation high speed production. (For the major manufacturers: lace factory, knitting factory, circular knitting machine, hosiery machine etc..)

The traction type waxing device, automatic rotation and automatic braking function ensure the waxing amount of the yarn, so as to obtain the best winding effect. It is ideal for winding cotton, linen, silk and chemical fibers.

Technical characteristics	Technical Parameters
Grooved drum	Ø/D 82mm, pitch 2.5, symmetrical 0°
Take-up package	0° Cylindrical tubes, or conical 5° 30° 4° 20°
Automatic length fixing	Electronic winding length setting based on finished product, max. 399999m
(Selection) Slow start	For smooth start and better winding quality
Yarn brake with weights	It avoids the fluttering of the feeding yarn, provide suitable winding tension
Electric waxing device	Adjusting the clearing gap, makes yarn smooth and fabric soft
Configuration	8 spindles / section
Composition	Max. : 18 sections / set (108 spindles)
Motorization	1 coaxial 3phased DC motor per spindle, controlled by 1 inverter in each line of 54 spindles
Max. speed	1100m /min
Traverse	Standard 14.7mm
Balancer	The winding pressure can be controlled by balance of spring
Yarn detector	With optical sensor
Max. package	250mm
Start / stop	By film switch, general control for single side by LCD
Radial anti patterning system	The anti patterning parameter is controlled by computer
(Selection) Blowing and suction cleaner	1100W motor power of cleaner
Absorbed power	100W per spindle at max. speed, excluding the motor power of cleaner
Power supply	3 phased 400V ± 10%, 50/60Hz
Machine (8 spindles) weight and dimension	350kg 1900mm (length) × 1100mm (width) × 1400mm (height) One-sided machine
(Selection) Weight for cleaner	132 kg According to spindle quantity
Lighting system	Lamp
Air splicer	Ordered separately
Length calculator	Can setting the yarn length

Note :

Due to keeping innovation, the specification and Machine pictures or color are subject to alteration without notice!